

SRT 405/405i

SRT405/405i are modern, high quality lone worker alarms, future-proofed with both LTE and GSM connectivity.

SRT405/405i is the result of years of experience developing lone worker alarms and comes fully loaded with handy functions.

Alarm types

SRT405/405i can handle a range of different alarm types. The big red button is normally used for emergency situations. Pressing the button causes an alarm message to be sent to the alarm receiver of your choice, while simultaneously establishing a voice call, all in order to enable quicker emergency response.

The two function buttons can be used for less critical situations or for communicating with secondary alarm receivers. Automatic alarm types such as ManDown (based on the device rotation) and Timer-alarm (timer based alarm) are also supported.

Display

SRT405/405i is equipped with a display for easy interaction with the device. The device menu allows you to change settings and view status messages. During an emergency situation, all device events are clearly displayed.

Positioning

SRT405/405i GNSS positioning supports the GPS, GLONASS and Galileo satellite systems. The SRT405i also supports indoor positioning based on radio communication over the ISM band (requires the use of SRT's IPS network products) is also supported. This enables positioning in environments where GNSS does not work.

Smart Power Save

To be able to utilize the active modules in the alarms more efficiently we have developed functions for intelligent power usage. For detailed information read the product sheet for Smart Power Save.

Reporting

With SRT405/405i you can choose the report format that suits your needs. It supports many standard formats and the possibility to create completely custom formats. Alarm reports can be sent to up to 10 SMS receivers, 10 non-persistent TCP receivers and 3 persistent TCP receivers, making the SRT406/406i perfect for use cases requiring redundant communication.



- 4G LTE and 2G GSM/GPRS/EDGE
- Voice over LTE (VoLTE) with 2G-backup
- Display
- Up to 48 hours battery lifetime
- Speaker and microphone
- Motion detection
- 99 channels simultaneous GPS/GLONASS/Galileo-receiver
- Indoor positioning (SRT405i)
- Smart Power Save
- Multiple alarm types
- Dust and water protection (IP67)
- Dimensions: 60x46x20 mm
- Weight: 54 grams



Scandinavian Radio Technology AB
Krossgatan 18
SE - 162 50 Vällingby
Sweden

Contact us
Tel +46 8 620 29 60
E-mail sales@srt.se